



Antistatic bubble bags are manufactured from low-density polyethylene film modified to be antistatic and pink. The air bubbles in the material cushion shock and vibration. The bags have various uses in ESD protected areas:

- To contain non ESD sensitive items
- Separation of ESD sensitive and non sensitive items
- To offer physical protection to finished goods
- Transfer non ESD sensitive items from the EPA for primary packaging

Technical properties

- Made from tough medium duty 50gsm film
- Amine free polyethylene
- Soft and flexible; wraps around products for best protection.
- Surface resistance: $R_s < 1 \times 10^{10}$ to $< 1 \times 10^{12}$ ohms tested per IEC 61340-2-3
- Static decay: $< 2s$ from 5000V to 37V at 37°F (22°C) @ 15% rH per US Federal Test Method Standard 101C, Method 4046
- Bubble diameter: 10mm
- Bubble height: 4.5mm

Bags are supplied unprinted, not labelled and loose (not bundled).

Item	Size (W x L)
202515	130 x 185mm (6" x 8")
202520	180 x 235mm (6" x 10")
202530	280 x 360mm (8" x 10")

"Packaging used within an EPA shall consist of dissipative or conductive materials for intimate contact." [EN 61340-5-3 Clause 5.2 Inside an EPA]

"Transportation of sensitive products outside of an EPA shall require packaging that provides both:

- a) dissipative or conductive materials for intimate contact;*
 - b) a structure that provides electrostatic discharge shielding."*
- [EN 61340-5-3 Clause 5.3 Outside an EPA]



Made in the United Kingdom

Unless otherwise noted, tolerance $\pm 10\%$
Specifications and procedures subject to change without notice.

Antistatic Pink Bubble Bags

DESCO EUROPE

DESCO EUROPE
2A DUNHAMS LANE, LETCHWORTH GARDEN CITY,
HERTFORDSHIRE, SG6 1BE, UK
PHONE: +44 (0) 1462 672005
E-MAIL: Service@DescoEurope.com, INTERNET: DescoEurope.com

Drawing Number
202505

DATE:
December
2017