



- A. Humidity indicator cards allow fast visual inspection of the relative humidity within packaging and containers. The indicators quickly and clearly change from blue to pink as relative humidity increases to unsafe levels. Indicator spots are reversible.
- B. The cards can measure RH levels from 5% to 60%.
- C. Components: Blotter paper IAW UU-P-63, CoC12 <0.1% (conforms to European directive 98/98), Proprietary ingredients; Printing design: one colour, black ink
- D. Indicator spots chemically impregnated onto blotter paper. Manufactured IAW MIL-I-8835
- E. Temperature correction factor: 2.5% RH per -12°C above or below baseline temperature of 24°C
- F. Accuracy: ± 2.5% RH
- G. Shelf life is 5 years for an unopened unit container. Shelf life warranty applies only to the accuracy of indicating spots. This warranty does not guarantee that all indicating spots will be blue upon initial opening of the can.
- H. Dimensions: 40 x 120mm; Humidity indicator range at 75°F: 10, 20, 30, 40, 50, 60% RH
- I. Meets IPC/JEDEC J-STD-033 Specifications issued May 1999.

Item	Description
204502	Humidity Indicator Cards, 6 Spot, 40 x 120mm, Can of 200



Made in Britain

Specifications and procedures subject to change without notice.

Vermason

Humidity Indicator Cards

VERMASON
 UNIT C, 4TH DIMENSION, FOURTH AVENUE, LETCHWORTH,
 HERTS, SG6 2TD UK
 PHONE: +44 (0) 1462-672005, FAX: +44 (0) 1462-670440
 E-MAIL: Service@Vermason.co.uk, INTERNET: Vermason.co.uk

Drawing Number
 204502

DATE:
 July
 2010