



Description

- Static dissipative
- Two-layer matting with excellent heat and chemical resistance
- Top layer is static dissipative and is connected to the conductive underside
- Can be laid loose or bonded in place with conventional rubber adhesive or double sided adhesive tape
- No carbon on top surface
- Withstands chair castors
- Available as mats or rolls
- Mats have two studs on long side



Specifications

R_G : 10E5 to 10E7 ohms meets EN 61340-5-1

R_S : 10E5 to 10E7 ohms meets EN 61340-5-1

Thickness: 2.5mm

Weight: 3.6kg/m²

Colour: Beige, Blue, Grey

ESD flooring meets EN 61340-5-1 Edition 1.0 2007-08 tested per IEC 61340-4-1

“The use of floor materials to control personnel or equipment generated static has a number of benefits. Floor materials tend to be passive. Employees who work in areas protected with floor materials simply need to wear and test the appropriate footwear. They do not need to implement any additional actions themselves to assure that the floor material is functioning properly.

Floor materials, particularly floor coverings, finishes, and coatings, can be applied or installed throughout the work environment providing a broad area of control rather than isolated control at individual workstations. They improve the mobility of personnel who work in the environment. Finally, floor materials can help control static on trolleys or other mobile equipment if properly grounded.” [CLC/TR 61340-5-2:2008 User guide clause 4.7.3.4 Benefits of floor materials]



Made in Britain

ITEM	DESCRIPTION
210930	Mat, 1.5M x 1.2M, Beige
210931	Mat, 1.5M x 1.2M, Blue
210932	Mat, 1.5M x 1.2M, Grey
210935	Mat, 1.8M x 1.2M, Beige
210936	Mat, 1.8M x 1.2M, Blue
210937	Mat, 1.8M x 1.2M, Grey
210940	Roll, 1.2M x Up to 10M long, Beige
210941	Roll, 1.2M x Up to 10M long, Blue
210942	Roll, 1.2M x Up to 10M long, Grey
210945	Full Roll, 1.2M x 10M, Beige
210946	Full Roll, 1.2M x 10M, Blue
210947	Full Roll, 1.2M x 10M, Grey

Norastat® Dissipative Rubber Floor Matting

VERMASON
 UNIT C, 4TH DIMENSION, FOURTH AVENUE, LETCHWORTH,
 HERTS, SG6 2TD UK
 PHONE: +44 (0) 1462-672005, FAX: +44 (0) 1462-670440
 E-MAIL: Service@Vermason.co.uk, INTERNET: Vermason.co.uk

Drawing Number
 210930

DATE:
 July 2009