



- 2.4 PVC insulation
- Conductor is high strength 7-strand tinsel wire for strength and durability
- Right angled plug protrudes less, less likely to be bent or snagged
- 2mm diameter cord with black polyurethane insulation
- 1 M Ω (1x10E6 ohms) resistor built in to socket

ITEM	CODE	DESCRIPTION
230290	J4292	1.8m Coiled Cord, 10mm Socket / 4mm Angled Male Plug
230295	J4294	1.8m Coiled Cord, 4mm Socket / 4mm Angled Male Plug

"The primary means of grounding personnel shall normally be by a wrist strap connected to an EBP (Earth Bonding Point)." "The wrist strap shall consist of a band that fits snugly around the wrist and a cord to connect the band to an EBP. ..The cord shall have a termination compatible with the EBP and shall incorporate at least one insulated current-limiting resistor. The total resistance from hand to EBP shall be in accordance with table 1 (Rg 7,5 x 10E5 to 3,5 x 10E7 ohms)." (EN 61340-5-1 paragraph 5.5 and 5.2.7)

"A nominal 1 megohm resistor is commonly used in wrist straps and to ground work surfaces." (EN 61340-5-2:Section 5.1.1)



Made in Britain

Vermason

Coiled Cords with Angled Plug

VERMASON
UNIT C, 4TH DIMENSION, FOURTH AVENUE, LETCHWORTH,
HERTS, SG6 2TD UK
PHONE: +44 (0) 1462-672005, FAX: +44 (0) 1462-670440
E-MAIL: Service@Vermason.co.uk, INTERNET: Vermason.co.uk

Drawing Number
230290

DATE:
December 2008