



[231280](#)

## Description

- 2.4mm PVC insulation
- Conductor is high strength 7-strand tinsel wire for strength and durability
- Low-profile conical head helps prevent cord from being knocked off
- Built-in 10mm stud fits socket on mat
- 1 megohm ( $1 \times 10^6$  ohms) current limiting resistor in conical head end
- Made in Taiwan

ITEM	DESCRIPTION
<a href="#">231265</a>	10mm Socket, M5 Ring Terminal, 1.7m, No Resistor
<a href="#">231267</a>	10mm Socket, 10mm Socket, 0.25m, 1 Megohm ( $1 \times 10^6$ ohms)
<a href="#">231280</a>	10mm Socket, M5 Ring Terminal, 4.5m, 1 Megohm ( $1 \times 10^6$ ohms)

“EPA ground cords shall be used to make electrical connections between groundable points and the EPA ground facility.

Where a single resistor is used in the EPA ground cord, this shall be located near the groundable point. Where more than one resistor is used, a resistor of a minimum resistance value of one half the total resistance shall be located near the groundable point.

When accessible, the EPA ground cord and its groundable point connection shall be shrouded by insulating material.” (EN 61340-5-1 section 5.3.4 EPA ground cords)

*Unless otherwise noted, tolerance  $\pm 10\%$*

Specifications and procedures subject to change without notice.

# Vermason

## Straight Cords with Conical Head, 10mm Socket

VERMASON  
UNIT C, 4TH DIMENSION, FOURTH AVENUE, LETCHWORTH,  
HERTS, SG6 2TD UK  
PHONE: +44 (0) 1462-672005  
E-MAIL: [Service@Vermason.co.uk](mailto:Service@Vermason.co.uk), INTERNET: [Vermason.co.uk](http://Vermason.co.uk)

Drawing Number  
**231265**

DATE:  
April 2014