



- A. Vermason Dissipative Document Wallets are designed for use within ESD Protected Areas in accordance with EN 61340-5-1. Unprotected documents could hold electrostatic charges that may cause damage to electrostatic sensitive devices.
- B. The pocket provides mechanical protection to contents. Documents are inserted into the pocket, which can be clipped into a 2, 3 or 4-ring binder such as Vermason Dissipative Ring Binders.
- C. Inherently static dissipative, charges removed to ground when placed on a grounded working surface or handled by a grounded operator. Dry to the touch, the pocket opens at the top. They are no stick and suitable for photocopies and fax.
- D. During normal use the Dissipative Document Wallet is low charging antistatic.
- E. They are made of polyethylene modified using durAstatic® technology. These document wallets do not contain additives that bloom to the surface or that are volatile and are therefore suitable for use in clean rooms.
- F. The spine of the pocket is reinforced and has eleven holes.

**Film properties**

Property	Value	Test Method
<b>Film thickness</b>	75 micron (75 micrometre or .003")	
<b>Weight per 100±7%</b>	1.2kg	
<b>Surface resistance @ 22°C / 15% rH (EN 61340-5-1)</b>	1x10E5 </= Rs <1x10E11 ohms	IEC 61340-2-3
<b>Charge decay time @ 22°C / 15% rH (EIA 541 app. F)</b>	T <sub>1000</sub> <2s	
<b>Colour</b>	clear, transparent	

Item	Insert Size	External Size h x w	Spine	Unit
<a href="#">238755</a>	A4 Portrait 210 x 297mm	306 x 233mm	11-hole	100

EN 61340-5-1 "Paperwork inside the EPA shall either be kept in containers conforming to the requirements of table 2 or shall not generate a field in excess of that specified in paragraph 5.3.5 (ESDS should not be exposed to electrostatic fields in excess of 10 kV/m)." Insulative paper, placed upon ESD protected worksurface, can easily interrupt path-to-ground.



Made in Britain

Dimension tolerance: ±10%

Specifications and procedures subject to change without notice

# Vermason

## Dissipative Document Wallet

**VERMASON**  
 UNIT C, 4TH DIMENSION, FOURTH AVENUE, LETCHWORTH,  
 HERTS, SG6 2TD UK  
 PHONE: +44 (0) 1462-672005, FAX: +44 (0) 1462-670440  
 E-MAIL: [Service@Vermason.co.uk](mailto:Service@Vermason.co.uk), INTERNET: [Vermason.co.uk](http://Vermason.co.uk)

**Drawing Number**  
**238755**

**DATE:**  
 June  
 2010