



- **Use with Wescorp and other brand antistatic tapes**
Can be used with standard 76mm core tapes.
- **Groundable housing and hardware**
Components of ESD tape dispenser can be grounded with ground cord (or through work surface*) to be used in ESD protected area.
- **Stainless steel construction**
Minimises foreign objects debris, corrosion, and other contamination when used in clean or sensitive areas. Simplifies cleaning.
- **Two separate spools turn independently**
Holds one 50mm wide roll of tape or two rolls of tape that are 25mm or less widths, depending on needs.
- **Heavy weighted design**
Extra weight allows for one-handed use; dispenser will not slide on most surfaces.
- **Grounding jack**
For operator personnel grounding with wrist strap or other grounding requirements.

Pictured with two 25mm wide tape rolls (not included).
Will accommodate up to one 50mm wide roll.

*Best practice is grounding via supplied ground cord. Attach cord to snap on chassis and to common ground point. If grounded via placing on a grounded ESD work surface, resistance to ground (Rg) should be periodically tested $<1 \times 10^9$ ohms.

“Avoid a discharge from any charged, conductive object (personnel and especially automated handling equipment) into the ESDS. This can be accomplished by bonding or electrically connecting all conductors in the environment, including personnel, to a known ground or contrived ground (as on board ship or on aircraft).” [EN 61340-5-1 Introduction]

Item	Description
242256	ESD Tape Dispenser, 50mm Wide x 76mm Core

Unless otherwise noted, tolerance $\pm 10\%$.
Specifications and procedures subject to change without notice.



Made in the
United States of America

DESCO EUROPE

ESD Tape Dispenser, 50mm

DESCO EUROPE
2A DUNHAMS LANE, LETCHWORTH GARDEN CITY,
HERTFORDSHIRE, SG6 1BE, UK
PHONE: +44 (0) 1462 672005
E-MAIL: Service@DescoEurope.com, INTERNET: DescoEurope.com

Drawing Number
242256

DATE:
January
2018