



Listing #90P1



Made in America

Description:

The [249250](#), [249251](#), [249252](#), and [249253](#) Foot Grounders provide contact with the ESD floor both under the foot's sole as well as the heel area, providing a more continuous and reliable path-to-ground. These foot grounders are easier to install than most foot grounders and are designed for use on standard shoes. The snug, reliable fit can be easily adjusted to fit the individual wearer. These foot grounders are made from non-marking three layer high visibility yellow reversible static dissipative rubber with a black conductive inner layer. The [249250](#), [249251](#), [249252](#), and [249253](#) are all UL listed. The product has been tested to ANSI/ESD STM 97.2 – Floor Materials and Footwear Voltage Measurement in Combination with a Person. It is a suitable ESD footwear component in Flooring / Footwear System when used as the primary grounding method (3.5×10^7 ohms per ANSI/ESD STM 97.1 Floor Materials and Footwear-Resistance Measurement in Combination with a Person.)

Components:

- A. 0.152cm \pm 10% thick non-marking, solid, three layer, rubber material. Three layers consist of a yellow dissipative outer layer with a black conductive inner layer, and a yellow dissipative outer layer. Will not mar floors or shoes with black marks.
- B. 0.952cm wide, 45.72cm long blue nylon ribbon contains 8 electrically conductive carbon suffused fibers, reversible, may be positioned on either side of foot.

listed for safety and date coded.

Tab to floor contact point:

>7.5 X 10E5 and <1.0 X 10E7 ohms resistance when measured per ESD SP9.2

Our UL listed foot grounders are rated at 250 VAC. It is not recommended to use them where exposure to line voltages above 250 VAC is possible. Caution: The foot grounder is for ESD control. It will not reduce or increase your risk of receiving electric shock when using or working on electrical equipment.

*U.S. Patent Number 5,786,977

RoHS Compliance Statement
None of the following materials are intentionally added in manufacturing this product: lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls (PBB) or polybrominated diphenyl ethers (PBDE) as outlined in the Directive 2002/95/EC Article 4.1. See Desco Industries Inc. letter and limited warranty on-line at Vermason.co.uk.

Item No.	Description	Recommended Shoe Size (Men)	Recommended Shoe Size (Women)
249250	Small	5-6	3.5-5.5
249251	Medium	6-8	5.5-7.5
249252	Large	8-11	7.5-9.5
249253	XLarge	12+	10.5+

Full Coverage Non-Marking Foot Grounder

VERMASON
UNIT C, 4TH DIMENSION, 4TH AVENUE LETCHWORTH,
HERTFORDSHIRE, SG6 2TD UK
PHONE: +44 (0) 1462-672005, FAX: +44 (0) 1462-670440
E-MAIL: Service@Vermason.co.uk, INTERNET: Vermason.co.uk

DRAWING NUMBER
249250

DATE:
November
2009