



Palm Side

Back Hand Side

Description

The Menda Dissipative Nylon Gloves with a Foamed Polyurethane Coating are designed as a low sloughing glove for photo handling, and can be used in many other industrial applications. They protect the operator's hands and film or product being handled. These gloves have the palm and fingers coated with polyurethane to minimize fingerprints and scratches on film or other products. Form fitting gloves combine excellent tactile feel with slip resistant coating and are also ideal for handling circuit boards.

The Menda Dissipative Nylon Gloves with Polyurethane Coating have ESD control properties of low charging and dissipative, addressing ElectroStatic Attraction problems from particles, and have good ventilation minimizing sweat and clamminess.

They are sold in pairs.

Features

- Nylon knitted glove is form fitting, comes in 5 sizes
- Non-slip polyurethane coated palm and fingers
- Low dust and lint sloughing - choice for photo handling and other applications
- Good elasticity and ventilation, minimizing sweat build-up
- Thickness: 1mm ± 0.2mm
- Fabric: Carbon Yarn 20% + Nylon Yarn 80%
- Resistance $1 \times 10^5 < 1 \times 10^9$ ohms, tested per ANSI/ESD SP15.1 Standard Practice for In-Use Resistance Testing of Gloves and Finger Cots

Glove Laundering

For proper operation, the ESD Gloves must be laundered periodically. Woolite works well. Liquid detergents are better than dry detergents in that there is less caking and frictional wear. Launder glove in cool or warm water, tumble dry with low heat or hang dry. Machine washing works well if using a standard home machine on gentle cycle. It is not recommended to launder these gloves in heavy industrial laundry machines as it will lead to premature wear. Gloves should be tumbled dry using low heat. DO NOT BLEACH. After laundering, verify $R_{tt} 1 \times 10^5 < 1 \times 10^9$ ohms.

*Not recommended for use above 104°F (40°C)

Item	Size	Cuff Color
35669	X-Small	Orange
35670	Small	Grey
35671	Medium	Green
35672	Large	Brown
35673	X-Large	Yellow

TEST REPORT - EN 388	
The samples submitted were tested in accordance with EN 388 :	
Test Method	Performance Level
6.1 Abrasion Resistance	4
6.2 Blade Cut Resistance	1
6.3 Tear Resistance	3
6.4 Puncture Resistance	1

Specifications and procedures subject to change without notice

Dissipative Nylon Gloves with Polyurethane Coating

3651 WALNUT AVE., CHINO, CA 91710
 PHONE: (909) 627-2453
 WEBSITE: MendaPump.com

DRAWING NUMBER
35670

DATE:
June
2013

