

Description:

Protektive Pak foams contain no chlorofluorocarbons (CFCs) and are environmentally safe process available in the polyurethane foam industry today. This unique manufacturing process produces a wide range of high-quality versatile foam products without creating and releasing CFC's into the atmosphere.




Features:

- Static dissipative polyurethane <math><10E11</math> ohms
- Antistatic low charging, minimizing electrostatic charge generation
- Reduces stress from physical shock
- Easy to adapt for custom uses by die-cutting, laminating, etc.
- 1.4 lb/ft density
- Open cell material

Specifications:

Property	Test Method	Results
Density	ASTM D3574	1.4 lbs/ft
Firmness (ILD)	ASTM D3574	32-39 lbs/50 sq in.
Tensile Strength	ASTM D3574	12 lbs/sq in.
Tear Strength	ASTM D3574	1.2 lbs/lin in.
Elongation	ASTM D3574	150%
Pilability	Mil-P26514F	Excellent
Clickability	ASTM D257	Excellent
Surface Resistivity	FTMS 101c Method 4046	10E11 ohms/sq
Static Decay	FTMS 101c Method 3005	<math><2</math> sec
Melting point	N/A	350-375°F
Color	N/A	Pink

Item No.	Size
37710	1/4" x 40" x 48"
37711	1/2" x 40" x 48"
37712	3/4" x 40" x 48"
37713	1" x 40" x 48"



Made in America

Pink Cushion Grade Static Dissipative Foam

PROTEKTIVE PAK
BURIED SHIELDING LAYER

PROTEKTIVE PAK
 13520 MONTE VISTA AVENUE, CHINO, CA 91710
 PHONE (909) 627-2578, FAX (909) 363-7331
 ProtektivePak.com

DRAWING NUMBER
 37710

DATE:
 September
 2008