



Made in the
United States of America

Features

- Provides physical protection, with conductive material providing reliable path-to-ground
- Many sizes available
- Shipped knocked-down; easy to assemble
- Conductive 1×10^2 to $< 1 \times 10^5$ ohms material provides reliable path-to-ground
- Superior strength and durability; made from extruded, high impact polypropylene materials
- Chemical and moisture resistant
- Ideal for use where corrugated and/or paper products cannot be used
- Economical alternative to injection molded products
- Reusable, ensuring best value*
- Made in the United States of America

Specifications

| Properties | Typical Values |
|-----------------------|------------------------------------------------------------------------------|
| Resin Type | Polypropylene |
| Conductive | Permanently |
| Surface Resistance | 1×10^2 to $< 1 \times 10^5$ ohms per ANSI/ESD STM11.11 and ESD TR53 |
| Humidity Independent | Yes |
| Temperature Tolerance | -17° F to +230° F |
| Melting Point | 324° F |

| Item | L x W x D (IN) | L x W x D (MM) |
|-----------------------|----------------|-----------------|
| 38900 | 12 x 2 x 4 | 305 x 51 x 102 |
| 38901 | 12 x 4 x 4 | 305 x 102 x 102 |
| 38902 | 12 x 6 x 4 | 305 x 152 x 102 |
| 38903 | 12 x 8 x 4 | 305 x 203 x 102 |
| 38904 | 18 x 4 x 4 | 457 x 102 x 102 |
| 38905 | 18 x 6 x 4 | 457 x 152 x 102 |
| 38906 | 18 x 8 x 4 | 457 x 203 x 102 |
| 38907 | 24 x 4 x 4 | 610 x 102 x 102 |
| 38908 | 24 x 6 x 4 | 610 x 152 x 102 |
| 38909 | 18 x 2 x 4 | 457 x 51 x 102 |
| 38910 | 24 x 2 x 4 | 610 x 51 x 102 |
| 38911 | 12 x 12 x 4 | 305 x 305 x 102 |
| 38912 | 18 x 12 x 4 | 457 x 305 x 102 |

RoHS 2 and REACH Compliance Statement

None of the RoHS 2 restricted materials or REACH substances of very high concern as of 2013/06/20 are intentionally added in manufacturing this product. Ref: European Union Directive 2011/65/EU and Regulation (EC) No. 1907/2006/CE. See Protektive Pak [Limited Warranty at ProtektivePak.com](#).

Per Packaging standard ANSI/ESD S54.1 section 6.1. Inside an ESD Protected Area "Packaging used within an EPA (that satisfies the minimum requirements of ANSI/ESD S20.20) shall be:

1. Low charge generation.
2. Dissipative or conductive materials for intimate contact."

Unless otherwise noted, tolerance $\pm 10\%$

Specifications and procedures subject to change without notice.

Plastek™ Open Bin Boxes

PROTEKTIVE PAK
13520 MONTE VISTA AVENUE, CHINO, CA 91710
PHONE (909) 627-2578
[ProtektivePak.com](#)

DRAWING NUMBER
38900

DATE:
January
2014

PROTEKTIVE PAK