

Item	Description	Qty/Roll
<u>47500</u>	2" x 2"	500
<u>47507</u>	2" x 2", Re-usable	500

RoHS Compliance Statement

None of the following materials are intentionally added in manufacturing this product: lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls (PBB) or polybrominated diphenyl ethers (PBDE) as outlined in the Directive 2002/95/ FC Article 4.1. See Desco Industries Inc. letter on-line at ProtektivePak.com.

COLOR: Yellow with black printing

SYMBOL: RS-471, Symbol is same as ESD Association ESD

Susceptibility symbol per ANSI/ESD S8.1

PACKAGED: 500 per roll. 3" diameter core. Date/Lot Coded for QC Traceability

Pressure sensitive labels are designed to call immediate attention to items that are susceptible to damage from ESD. Permanent and reusable adhesive labels are designed for use on packages, containers, and anywhere a permanent or removeable and reusable warning is required. Labels are coated with varnish for added durability.

PAPER SPECIFICATIONS:

Facestock: 60# SemiGloss Litho

Adhesive: B-82 - Removeable and Reusable

B-82 - Permanent

40# RL Liner:

INK & VARNISH SPECIFICATIONS:

Water Resistance: Excellent Grease Resistance: Excellent Alcohol Resistance: Excellent

Per ANSI/ESD S8.1 section 3.1 ESD Susceptibility Symbol Application states 1 "The ESD susceptibility symbol should be used on assemblies and devices that have a sensitivity to ESD events." and, "The symbol may be incorporated on a sticker used to close or seal ESD protective packaging to indicated that materials inside the package are ESD susceptible.

Unless otherwise noted, tolerance is ± 10%

Specifications and procedures subject to change without notice.

LABEL, SUSCEPTIBILITY, RS-471



PROTEKTIVE PAK

13520 MONTE VISTA AVENUE, CHINO, CA 91710 PHONE (909) 627-2578, FAX (909) 363-7331 ProtektivePak.com

DRAWING NUMBER 47500

DATE: November 2011