



Item	Description
60099	Disposable Wrist Strap

Tolerance: ± 5%

### Description

The Disposable Wrist Strap provides an effective, economical alternative for single use personnel grounding meets EN 61340-5-1. The Disposable Wrist Strap can be shipped with ESD sensitive items whose manufacturer recommends that the installer of the item be grounded during installation so static discharge damage does not occur. Product is individually packaged for inclusion with customer's product if desired.

Custom printing of logo on packaging is available. Contact Customer Service for details.

### Key

- A. 25 cm adhesive holds conductive strip in contact with wearer to wrap 360° around operator's wrist. The adhesive is a waterbase acrylic.
- B. White insulative spunbonded polyester non-woven fabric outer material.
- C. Black resistive non-woven fabric provides a path to ground. Total resistance to ground is approximately 5 megohms to limit current in the event of accidental operator contact with equipment line voltage.
- D. Release paper is removed to expose adhesive on both ends.
- E. 10 cm grounding end of disposable wrist strap uses adhesive to secure conductive strip to bare grounding surface. The adhesive is a waterbase acrylic. To be effective this end needs to be attached to the ground.
- F. Underwriters Laboratory listing 90P1 -- rated for 250 volts AC.
- G. Packaging made with ESD protective Dissipative Material (<math>10^{11}</math> ohms)

Specifications and procedures subject to change without notice



Made in America



## Disposable Wristband

CHARLESWATER LTD.  
 UNIT 17. MILLBROOK BUSINESS PARK, SYBRON WAY  
 CROWBOROUGH, EAST SUSSEX TN6 3JZ UNITED KINGDOM  
 PHONE: 00 44 (0) 1892-665313, FAX: 00 44 (0) 1892-668838  
 INTERNET: [Charleswater.co.uk](http://Charleswater.co.uk)

**Drawing Number**  
 60099.E

**DATE:**  
 October  
 2010