



- 2.5mm polyurethane insulation
- Conductor is high strength 7-end duplex tinsel for strength and flexibility
- 1 megohm resistor built in each socket
- Colours: black and yellow
- Standard cords are marked and date coded
- Coiled Cords length nominal when extended

Item	Description
60220	1m Coiled Cord,10mm Socket / 10mm Socket, Yellow
60225	2m Coiled Cord,10mm Socket / 10mm Socket, Black
60226	2m Coiled Cord,10mm Socket / 10mm Socket, Yellow
60227	2m Coiled Cord,10mm Socket / 10mm Socket, Yellow, 2.2 meg
60228	2m Coiled Cord,10mm Socket / 10mm Socket, Yellow, 0 meg
60230	3m Coiled Cord,10mm Socket / 10mm Socket, Black

"EPA ground cords shall be used to make electrical connections between groundable points and the EPA ground facility.

Where a single resistor is used in the EPA ground cord, this shall be located near the groundable point. Where more than one resistor is used, a resistor of a minimum resistance value of one half the total resistance shall be located near the groundable point.

When accessible, the EPA ground cord and its groundable point connection shall be shrouded by insulating material." (EN 61340-5-1 section 5.3.4 ground cords)

Per Note 6 of Table 1 of EN 61340-5-1 for Working surfaces, storage racks, trolleys and carts "It is allowed, when approved by the ESD co-ordinator, to use surfaces which are 'hard ground' i.e. less than 1 X 10E4 ohms to EPA ground."

Tolerance: $\pm 10\%$

Specifications and procedures subject to change without notice.



Made in Britain



Coiled Cords, 10mm Socket, 10mm Socket

CHARLESWATER LTD.
 UNIT 17. MILLBROOK BUSINESS PARK, SYBRON WAY
 CROWBOROUGH, EAST SUSSEX TN6 3JZ UNITED KINGDOM
 PHONE: 00 44 (0) 1892-665313, FAX: 00 44 (0) 1892-668838
 INTERNET: Charleswater.co.uk

Drawing Number
 60220.E

DATE:
 June
 2010