



60222

- 2.5mm polyurethane insulation
- Conductor is high strength 7-end duplex tinsel for strength and flexibility
- 1 megohm resistor built into 4mm socket
- 4mm banana plug does not contain resistor
- 2m length nominal when extended
- Colours: black or yellow
- Dielectric Strength: Cords withstand 1250 volts DC for at least one minute
- Standard cords are marked and date coded



Per CLC/TR 61340-5-2:2008 User guide Wrist Strap clause 4.7.2.6 Summary

- Wrist straps provide an effective means for maintaining personnel at ground potential or at the same potential as the item(s) being handled. People who are at ground potential or a potential the same as the ESDS they are handling cannot discharge to the ESDS when it is handled or touched.
- Wrist straps usually have a current-limiting resistor, typically 1,0 x 10E6 ohm, molded into the ground cord near the point where the cord attaches to the cuff. The resistor usually has a working voltage rating of 250 V.
- Wrist straps are sometimes supplied with a 1,0 x 10E6 ohm resistor molded into both ends of the ground cord when both ends of the cord have the same type snap connector.
- Wrist straps should not be worn by personnel where they could come into contact with voltage over 250 V.
- Wrist strap ground cords should have a quick release connector to the cuff so personnel will not be tied to the workstation.
- Wrist strap bands should be worn comfortably snug around the wrist while making full skin contact.
- Wrist strap ground cords shall be connected to a groundable point or an equipotential bonding point. Do not connect to a snap on a dissipative mat unless it is the groundable point for the mat. Do not clip a wrist strap to the edge of a dissipative mat.
- Wrist straps should be tested on a regular basis with daily testing being recommended."

Item	Description	End 1	End 2
60222	2m coiled cord, black	10mm socket, 1 megohm resistor	4mm plug
60223	2m coiled cord, yellow	10mm socket, 2.2 megohm resistor	4mm plug
60224	2m coiled cord, yellow	10mm socket, no resistor	4mm plug

If not otherwise noted, tolerance ±10%

Specifications and procedures subject to change without notice.



Made in Britain



Coiled Cords, 10mm Socket, 4mm Plug

CHARLESWATER LTD.
 UNIT 17. MILLBROOK BUSINESS PARK, SYBRON WAY
 CROWBOROUGH, EAST SUSSEX TN6 3JZ UNITED KINGDOM
 PHONE: 00 44 (0) 1892-665313, FAX: 00 44 (0) 1892-668838
 INTERNET: Charleswater.co.uk

Drawing Number
 60222.E

DATE:
 October
 2010