



- 2.4mm PVC insulation
- Conductor is 1 x 7-ends/duplex tinsel (cadmium-free) for strength and durability
- < 2 ohms tested per Fluke ohmmeter per manufacturer's instructions
- Used to link two adjacent work surfaces
- No built-in resistors
- 2.5mm cord diameter, black PVC insulation

Item	Description
60272	Cord, Straight, 0.25m, 10mm Socket, 10mm Socket, No Resistor

"EPA ground cords shall be used to make electrical connections between groundable points and the EPA ground facility.

Where a single resistor is used in the EPA ground cord, this shall be located near the groundable point. Where more than one resistor is used, a resistor of a minimum resistance value of one half the total resistance shall be located near the groundable point.

When accessible, the EPA ground cord and its groundable point connection shall be shrouded by insulating material." (EN 61340-5-1 section 5.3.4 EPA ground cords)



Made in Britain



Link Cords, 10mm Socket, 10mm Socket

CHARLESWATER LTD.
UNIT 17, MILLBROOK BUSINESS PARK, SYBRON WAY
CROWBOROUGH, EAST SUSSEX TN6 3JZ UNITED KINGDOM
PHONE: 00 44 (0) 1892-665313, FAX: 00 44 (0) 1892-668838
INTERNET: Charleswater.co.uk

Drawing Number
60272.E

DATE:
July
2012