



[60285](#)



[60288](#)

Description

The EBP bar should be fixed to the edge of a bench or other suitable work equipment within reach and accessible to all connecting ground cords, but where it is unlikely to be knocked and damaged or hinder the operator.

Mount EBP bar with two M5 pan-head screws, minimum 12mm long.

Connect earthing cord to a suitable earth. A spare ring terminal is supplied if the cord needs to be shortened.

The bar is 72 x 37 x 38mm in size and is made of ABS. The yellow bar has a rear cover to prevent access to the resistors.

The bars are available with a variety of connectors: 4, 7 or 10mm stud 4mm female or male safety socket. Maximum three connectors per bar.

Resistors are usually built-in to each connector. The normal earth contact is linked via individual 1 megohms resistor rated at 1/2W. In the event of a workstation element becoming live the resistor will limit the fault current to less than 0.3mA at 240V. The resistor is capable of withstanding 500VDC for 6 minutes.

Item	Description
60285	EBP bar with 3 x 10mm Studs, Yellow, 3m Cord
60288	EBP bar with 3 x 4mm Plug Sockets, Yellow, 3m Cord

Specifications and procedures subject to change without notice.



Made in Britain



EBP Bars

CHARLESWATER LTD.
UNIT 17. MILLBROOK BUSINESS PARK, SYBRON WAY
CROWBOROUGH, EAST SUSSEX TN6 3JZ UNITED KINGDOM
PHONE: 00 44 (0) 1892-665313, FAX: 00 44 (0) 1892-668838
INTERNET: Charleswater.co.uk

Drawing Number
60285.E

DATE:
June
2010