

Jewel®



Notes:

"The primary means of grounding personnel shall normally be by a wrist strap connected to an EBP [Earth Bonding Point]." "The wrist strap shall consist of a band that fits snugly around the wrist and a cord to connect the band to an EBP. The wrist strap shall incorporate a quick release connection. The cord shall have a termination compatible with the EBP and shall incorporate at least one insulated current-limiting resistor. The total resistance from hand to EBP shall be in accordance with table 1 [Rg 7,5 x 10E5 to 3,5 x 10E7 ohms]." (EN 61340-5-1 clause 5.5 and 5.2.7)

"The term 'wrist strap' describes the combination of the wrist band, which should fit around the wrist making good skin contact, and the wrist cord which bonds the wearer to an earth bonding point. The wrist band will normally be worn for several hours at a time so it needs to be comfortable while making good contact with the skin. It is a good idea to check the wrist strap every time it is applied. Constant on line monitors can be used so that any breaks will be immediately found.

As a safety feature, the ground cord should release with a force of between 5 N and 25 N, preferably at the wrist band end." (EN 61340-5-2 paragraph 5.2.7 Wrist strap)

"Wrist straps shall be checked before use. Each check shall be made with the wrist band worn in contact with the wearer's skin and with the ground cord attached to the appropriate tester." (EN 61340 5 1 paragraph 9.6 Daily checks)

- **Revolutionary magnetic interconnect technology**  
Creates magnetic connection between wristband and coil cord; meets EN 61340-5-1 including safety disengagement force of 5 to 25 Newtons [1 to 5 pounds]. More consistent disengagement force than standard 4 mm designs.
- **Dual-wire wrist strap provides redundancy**  
If one dual wire wrist strap conductor is severed, operator still has reliable path-to-ground with other wire
- **3.5 mm mono plug compatible with 3M and other brand Continuous Monitors**
- **MagSnap revolutionary design provides consistent retention and release performance**
- **Comfortable, adjustable wristband**  
Made of silver suffused monofilament conductive interior
- **Woven Silveron™ fabric infused with silver monofilament conductive fiber**  
Reliably removes generated static charges and is hypo-allergenic
- **Adjustable**  
Only one item to stock; may be fitted to almost all people
- **Locking clasp**  
Band locked so it will not slip
- **UL Listed**  
CAUTION: The ESD Series is for electrostatic control. It will not reduce or increase your risk of receiving electric shock when using or working on electrical equipment. Follow the same precautions you would use without wrist straps, including:
  - Make certain that equipment having a grounding type plug is properly grounded.
  - Make certain that you are not in contact with grounded objects other than through the ESD Series.
- **Superior resistor connection strain relief**  
Superior reliability. Greatly exceeds ESD S1.1 Bending Life Test. Tested at over 11 million cycles vs. the 16,000 requirement
- **Covered by one or more of the following patents:**  
Wristband: 4,577,256; 4,639,825
- **Superior warranty**  
See details of 1 year Limited Warranty at [www.charleswater.co.uk/LimitedWarranty.aspx](http://www.charleswater.co.uk/LimitedWarranty.aspx)
- **Made in America**

ITEM	DESCRIPTION
<a href="#">60673</a>	Jewel® MagSnap Dual-Wire Adjustable Elastic Wristband
<a href="#">60674</a>	Jewel® MagSnap Dual-Wire Adjustable Elastic Wrist Strap with 1.8m Coil Cord
<a href="#">60675</a>	Jewel® MagSnap Dual-Wire Adjustable Elastic Wrist Strap with 3.65m Coil Cord

See Drawing [60670.E](#) for details on Jewel® MagSnap Dual-Wire Coil Cords

Improve wrist strap contact with Reztore™ ESD Hand Lotion.



Made in America

**Jewel® MagSnap Dual-Wire Adjustable Elastic Wrist Strap**

CHARLESWATER LTD.  
UNIT 17. MILLBROOK BUSINESS PARK, SYBRON WAY  
CROWBOROUGH, EAST SUSSEX TN6 3JZ UNITED KINGDOM  
PHONE: 00 44 (0) 1892-665313  
INTERNET: [Charleswater.co.uk](http://Charleswater.co.uk)

**DRAWING NUMBER**  
60673.E

**DATE:**  
August 2008

