



- A. Humidity indicator cards allow fast visual inspection of the relative humidity within packaging and containers. The indicators quickly and clearly change from blue to pink as relative humidity increases to unsafe levels. Indicator spots are reversible.
- B. The cards can measure RH levels from 5% to 60%.
- C. Components: Blotter paper IAW UU-P-63, CoC12 <0.1% (conforms to European directive 98/98), Proprietary ingredients; Printing design: one colour, black ink
- D. Indicator spots chemically impregnated onto blotter paper. Manufactured IAW MIL-I-8835
- E. Temperature correction factor: 2.5% RH per -12°C above or below baseline temperature of 24°C
- F. Accuracy: $\pm 2.5\%$ RH
- G. Shelf life is 5 years for an unopened unit container. Shelf life warranty applies only to the accuracy of indicating spots. This warranty does not guarantee that all indicating spots will be blue upon initial opening of the can.
- H. Dimensions: 40 x 120mm; Humidity indicator range at 75°F: 10, 20, 30, 40, 50, 60% RH
- I. Meets IPC/JEDEC J-STD-033

Item	Description
90069	Humidity Indicator Cards, 6 Spot, 40 x 120mm, Can of 200



Made in Britain

To have complete IPC/JEDEC J-STD-033B section 3.3 Dry Pack, use Humidity Indicator Card with Statshield Moisture Barrier Bags and Desiccant

Specifications and procedures subject to change without notice.



Humidity Indicator Cards

CHARLESWATER EUROPE LTD.
 UNIT 17. MILLBROOK BUSINESS PARK, SYBRON WAY
 CROWBOROUGH, EAST SUSSEX TN6 3JZ UNITED KINGDOM
 PHONE: 00 44 (0) 1892-665313, FAX: 00 44 (0) 1892-668838
 INTERNET: Charleswater.co.uk

Drawing Number
 90069.E

DATE:
 April
 2010