



### Description

- Synthetic rubber matting can be used in areas where molten solder or chemical spillages can occur
- Excellent heat and chemical resistance
- Mats have four 10mm studs

### Specifications

**R<sub>S</sub>:** 10E3 to 10E5 megohms meets EN 61340-5-1

**R<sub>G</sub>:** 10E3 to 10E6 ohms meets EN 61340-5-1

**Thickness:** 1.5mm

**Weight:** 2.2 kg/m<sup>2</sup>

**Heat Resistance:** >100°C

**Colour:** Black

EN 61340-5-1 paragraph 5.2.2 Working surfaces and storage racks "All working surfaces and storage racks on which unprotected ESDS may be placed shall be capable of being connected to EPA ground and shall have a point-to-point resistance and resistance to EPA ground in accordance with table 1 [Rp greater or equal to 1 x 10E4, less than or equal to 1 x 10E9 ohms, and Rg greater or equal to 7.5 x 10E5 to less than or equal to 1 x 10E9 ohms]."

ITEM	CODE	DESCRIPTION
228220	J0664	Mat, 1.2 x 0.6m
228210	J0657	1.2m wide, up to 10m long
228205	J0656	Roll, 1.2m wide x 10m
228200	J0655	Roll, 0.6m wide x 10m



Made in Britain

# Vermason

## Conductive Neoprene Rubber Matting

VERMASON LTD.  
 UNIT C, 4TH DIMENSION, FOURTH AVENUE, LETCHWORTH,  
 HERTS, SG6 2TD UK  
 PHONE: +44 (0) 1462-672005, FAX: +44 (0) 1462-670440  
 E-MAIL: Service@Vermason.co.uk, INTERNET: Vermason.co.uk

Drawing Number  
 TD-7518

DATE:  
 December  
 2008