



- A. Right angle barrel type banana plug with **machined contour spring support\***. Fits industry standard banana jack  $\geq 0.157"$
- B. Crimped termination to stranded conductor.
- C. Thermoplastic elastomer strain relief molded on. Flex life average  $>10,000,000$  cycles (ESD-S1.1). Break load average 30 pounds.
- D. Grey polyurethane wire insulation. Rapid retraction coil cord compresses length with resulting benefit of less tangling and dragging along work surface. Break load average 30 pounds.
- E. Tinsel conductor. Consisting of polyester wrapped with copper. High flex life. Equivalent is 29 gauge (cir mil and/or ohms).
- F. Autosplice brass crimp secures conductors to resistor lead and provides stress relief for resistor.

- G. One megohm  $\pm 5\%$ , 1/4 watt, series resistor limits current for operator safety.
- H. Spring loaded 7mm Item 23500, 23515) or 4mm (Item 23600, 23615) medical snap socket. Spring separation 0.125" - 0.165". Provides 1-5 pound breakaway from .160" snap stud (ESD S1.1). Compatible with most major brands.
- I. ESD Systems.com logo molded in compliance with ESD S1.1.
- J. Date coded with date of manufacture. Arrow points to month of manufacture (12:00 = December), numerals indicate the year (03=2003).
- K. Underwriters Laboratory Listing 1J92 when used with ESD Systems.com 20050, 20051, 21240, 21242, 22000, and 22005 wristbands.
- L. Right angle design has lower profile, making it less likely to be snagged and accidentally pulled out. Swivels on banana barrel for less strain - extending the life of the cord.
- M. Ribbed molding assists grasping of right angle banana plug. The plug will not be removed by tugging on cord.

\*U.S. Patent 5951337

Item	Description
23610	Coil Cord, 6', Angle Banana, 4mm
23612	Coil Cord, 10', Angle Banana, 4mm

## Ground Cord, Wrist Strap, Retractable, Coiled, Right Angle



ESD SYSTEMS.COM  
 432 NORTHBORO ROAD CENTRAL  
 MARLBORO, MA 01752 USA  
 TEL. (508) 485-7390 FAX (508) 480-0257



Visit our online  
 library of Tech Drawings:  
<http://www.esdsystems.com>

**DRAWING NUMBER**  
 TD-23610

**DATE**  
 07/04