

The Future of Fume Extraction

400

FEATURES

- Clear & informative graphic displa
- Highest grade HE A and carbon technology
- · Automatic electronic flow control maintains a constant extraction rate even as the filter blocks
- Gas and particle sensors to warn the operato
- Adjustable airflow

FILTERS

INCLUDED AS STANDARD...

Voltage	120v	230v
Volume Part Number	0LX4001D	0LX4000D
Vacuum Part Number	080411D	080410D
Wattage	1.2kW	1.2kW
Frequency	50Hz / 60Hz	50Hz / 60Hz
Cabinet Height	710mm	710mm
Cabinet Width	465mm	465mm
Cabinet Depth	528mm	528mm
Cabinet Weight	50kg	50kg
Sound Level	<60dBa	<60dBa
Airflow	400m3/h	400m3/h

SPECIFICATIONS



Main Filter Code 113505

Description HEPA/Chemical

Pre-filter Code 200025

Description F5 Pad

CONNECTION KIT

Connection kit is included see overleaf for options

OPTIONS



If you do not see a connection kit that fits your machine or pipework, please contact Purex or your representative

Interfacing



Interfacing can remotely start the Purex machine when the connected machine starts.

Interfacing can also warn the connected machine when the Purex machine is in alarm.

Take a look through our Interfacing Guide to see our extensive range of options



Purex Inc 2246 Palmer Drive, Suite 108 Schaumberg Illinois 60173 USA



APR is an authorized distributor of Purex Fume Extraction Systems 3651 Walnut Ave, Chino CA 91710 • Phone (909) 664-9980 • APR-Rework.com