



Specifications

Properties Resin Type Conductive Surface Resistance **Humidity Independent** Temperature Tolerance **Melting Point**

Typical Values Polypropylene Inherently 1×10^2 to $< 1 \times 10^5$ ohms 17° F to +230° F 324° F

Meets ANSI/ESD S20.20 and Packaging Standard ANSI/ESD S541

Features

- · Convenient storage tray made of conductive material, provide a reliable path-to-ground
- Includes steel wire frame which allows travs to stack, improving productivity and saving valuable space
- Static dissipative foam bottom laminated to Plastek™, provides ESD and shock protection
- Rs: 1×10^2 to $< 1 \times 10^5$ ohms per ANSI/ESD STM11.11, meets ANSI/ESD S20.20 and Packaging standard ANSI/ESD S541
- Printed with ESD protective symbol as required by ANSI/ESD S541
- Chemical and moisture resistant
- Ideal for use where corrugated and/or paper products cannot be
- Economical alternative to injection molded products
- Reusable, ensuring best value
- Product ships assembled
- Made in America

Item No.	Tray Size - L x W x D
<u>39160</u>	18" x 11-3/8" x 1-3/4"
<u>39161</u>	22-3/4" x 17" x 2-1/2"



If not otherwise noted, tolerance ±10% Specifications and procedures subject to change without notice.

PROTEKTIVE PAK

PLASTEK™ TEK TRAYS

PROTEKTIVE PAK

13520 MONTE VISTA AVENUE, CHINO, CA 91710 PHONE (909) 627-2578 ProtektivePak.com

DRAWING NUMBER 39160

DATE: April 2016