



# Blue

## Grounding & Cleaning

If the material is used on top of an already properly grounded surface, <u>grounding hardware</u> may not be necessary. Where no properly grounded surface is available, <u>grounding hardware</u> is required to provide a path-to-ground. Rg compliance verification measurements must be made per EN 61340-5-1 periodically with a <u>surface</u> resistance meter.

See Tech Bulletin <u>TB-7000</u> for Reztore<sup>®</sup> Surface & Mat Cleaner Application Instructions.

## Limited Lifetime Warranty:

Desco Europe warrants for one year that Statfree® matting products will be free of defects in materials and workmanship and will guarantee dissipative/conductive mat properties for the life of the mat. Damage to matting caused by misuse of any kind, including using inappropriate cleaners is not covered by <u>Desco</u><u>Europe Limited Warranty.</u>

#### RoHS 3, REACH, and Conflict Minerals Statement See the Desco Europe RoHS 3, REACH, and Conflict Minerals Statement: DescoEurope.com/ROHS.aspx

See the Deese Europe Limited Wa

See the Desco Europe Limited Warranty: <u>DescoEurope.com/Limited-Warranty.aspx</u>

See the Desco Europe Disclaimer: DescoEurope.com/Disclaimer.aspx

# **DESCO**EUROPE

# **Specifications**

Standard Document EN 61340-5-1

# **Electrical Properties**

**Property** Rp-p Resistance: Rg Resistance: Test Method IEC 61340-2-3 IEC 61340-2-3

## Meets Requirements of: Working Surface

**Value** 1 x 10<sup>6</sup> to < 1 x 10<sup>8</sup> ohms 1 x 10<sup>6</sup> to < 1 x 10<sup>8</sup> ohms

## **Physical Properties**

Construction:3-Layer vinylThickness:9.5mmColour:\*BlueTexture:\*Smooth finish

## Tolerances

Width  $\pm$  6.35mm Length  $\pm$  6.35mm for every 0.305m of running material.

Matting materials have a tendency to shrink slightly when first unrolled. In applications where length is critical, allow the material to relax for at least 4 hours before cutting to size. Always trim with a sharp knife or razor blade.

\*Colour and texture may vary between lots and mills

For product listings, please click Here.

Specifications and procedures subject to change without notice.

# Statfree O<sup>™</sup> Dissipative 3-Layer Vinyl

DESCO EUROPE 2A DUNHAMS LANE, LETCHWORTH GARDEN CITY, HERTFORDSHIRE, SG6 1BE, UK PHONE: +44 (0) 1462 672005 E-MAIL: Service@DescoEurope.com, INTERNET: DescoEurope.com

Drawing Number PME-O DATE: September 2017

© 2017 DESCO INDUSTRIES INC. Employee Owned