

SAFETY DATA SHEET

May be used to comply with OSHA Hazcom 29 CFR 1910.1200. Standards must be consulted for specific requirements.

Revision Date: 2020-03-27

1. IDENTIFICATION

Product identifier

Product Name: Statguard Flooring 8403 Conductive Epoxy Adhesive, Part A

Recommended use of the chemical and restrictions on use

Identified use: Epoxy Resin

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Supplier: MILAMAR COATINGS, INC
311 NW 122ND STREET, SUITE 100
OKLAHOMA CITY, OK 73114
405-755-8448

Email Address: Service@StatguardFlooring.com

Emergency 24 hour telephone number

Domestic Emergency Number 1-800-255-3924

International Emergency Number 1-813-248-0585

2. HAZARDS IDENTIFICATION

Classification of substance or mixture

Flammable liquid	Category 3
Acute Toxicity (Dermal)	Category 4
Acute Toxicity (Oral)	Category 4
Acute Toxicity (Inhalation)	Category 4
Skin Corrosion/Irritant	Category 4
Eye Damage/Irritation	Category 4

Label elements

Hazard pictograms/Symbols:



Signal word:

WARNING!

Hazard statements:

Flammable liquid and vapor.
Harmful in contact with skin.
Causes eye irritation.
Harmful if swallowed.
Harmful if inhaled.

Precautionary statements:

Prevention

Keep away from heat/sparks/open flames/hot surfaces. No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Wear protective gloves/eye protection/face protection.
Flush eyes thoroughly after eye contact.
Wash hands thoroughly after handling.
Do not eat, drink or smoke when using this product.

Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well ventilated area.

Response

If on skin (or hair): remove/take off immediately all contaminated clothing. Rinse skin with water/shower. In case of fire: use carbon dioxide, foam, dry chemical or water fog to extinguish fire.

If on skin: wash with plenty of soap and water. Call a poison center or doctor/physician if you feel unwell. Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Call a physician if irritation persists.

Wash contaminated clothing before reuse.

If in eyes: rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: get medical advice/attention.

If swallowed: Call a poison center or doctor/physician if you feel unwell. Rinse mouth.

Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area.

Storage

Store in a well-ventilated place. Keep cool.

Disposal

Dispose of contents/container in accordance with applicable regulations.

3. COMPOSITION/INFORMATION ON INGREDIENTS

This product is a mixture. Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

Components	CAS No.	Concentration
Reaction products of epichlorohydrin and bisphenol A	25085-99-8	70 - 80%
Epoxy resin	28064-14-4	10 - 15%
Amorphous silica	112945-52-5	< 5%
Ethanol	64-17-5	< 10%

4. FIRST AID MEASURES

Description of first aid measures

General advice:

First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation:

Remove victim to fresh air if effects occur. If not breathing, give artificial respiration. Get immediate medical attention.

Skin Contact

Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Call a Physician if irritation persists. Wash clothing before reuse. Contaminated Leather Articles, including shoes, cannot be econtaminated and should be destroyed to prevent reuse.

Eye Contact:

Remove contact lenses at once. Immediately flush eyes with large amounts of water or normal saline for at least 30 minutes. Hold eyelids apart while flushing to rinse entire surface of eye and lids with water.

Ingestion

Do not induce vomiting. If patient is conscious and can swallow, give two glasses of water (16oz.) Get immediate medical attention. Never give anything by mouth to an unconscious or convulsing person.

Most important symptoms and effects, both acute and delayed

Signs and Symptoms: Irritation as noted above. Skin sensitization (allergy) may be evidenced by rashes, especially hives.

Aggravated medical conditions: preexisting skin and eye disorders may be aggravated by exposure to this product. Preexisting skin and lung allergies may increase the chance of developing increased allergy symptoms from exposure to this product.

Other Health Effects: Based on animal studies, repeated exposure to components of this product may cause damage to liver, kidney, and respiratory systems. Reports have associated repeated and prolonged occupational exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling vapors may be harmful or fatal.

Indication of any immediate medical attention and special treatment needed

Contact a poison control center for additional treatment information. As a precaution, exposure to liquids, vapors, mists, or fumes should be minimized.

5. FIREFIGHTING MEASURES

Extinguishing media

Suitable Extinguishing Media Use alcohol type foam, dry chemical, or CO₂.

Unsuitable Extinguishing Methods None known

Special hazards arising from the substance or mixture

Flash Point is 93°F TCC.

Advice for firefighters

Fire Fighting Procedures: Use water spray to cool fire Exposed surfaces and to protect personnel. If a leak or spill has not ignited, use ER spray to disperse the vapors. Contain the runoff stream. Try to cover liquid pills with foam.

Special protective equipment for firefighters: Do not enter confined fire space without full bunker gear (helmet with face shield, bunker coats, gloves, and rubber boots), including a positive pressure IOSH approved self contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Ventilate the area.

Avoid breathing vapor.

Use self-contained breathing apparatus or supplied air for large spills or confined areas.

See protective measures under point 7 and 8

Methods and materials for containment and cleaning up

Contain spill if possible.

Wipe up or absorb on suitable material and pick up with shovels.

Do not use sawdust, wood chips, or other cellulosic materials to absorb the spill.

Prevent entry into sewers and waterways.

Dispose of in accordance with federal, state, and local regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Ground all transfer equipment.

Take precautionary measures against static discharge.

Handle as an industrial chemical.

See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Keep container tightly closed when not in use. Practice good caution and personal cleanliness to avoid skin and eye contact. Hold bulk storage under nitrogen blanket. Store in a cool, dry place with adequate ventilation. Keep away from open flames and high temperatures

See SECTION 8, for types of ventilation required.

8. EXPOSURE CONTROL / PERSONAL PROTECTION

Control parameters

Components	CAS No.	Exposure Limits	Source
Reaction products of epichlorohydrin and bisphenol A	25085-99-8	None established	
Epoxy resin	28064-14-4	None established	
Amorphous silica	112945-54-5	5 mg/m ³ TWA, Respirable	OSHA
Ethanol	64-17-5	1000 ppm TWA	OSHA

Appropriate engineering controls: N.A.

Individual protection measures

Eye/Face Protection	Use close fitting safety goggles, don't use eye lens.
Skin Protection	Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.
Hand Protection	Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.
Respiratory Protection	Provide adequate ventilation. Avoid breathing of vapors or mists. Airborne concentrations should be kept to lowest levels possible. When exposures are not adequately controlled, use an approved respirator. Selection of air-purifying or positive-pressure supplied air will depend on the specific operation and the potential airborne concentration of material. For emergency conditions, use an approved positive-pressure self-contained breathing apparatus.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state:	Liquid
Appearance and color:	clear/white paste
Odor:	Little to no odor
Odor threshold:	N/A
pH:	N/A
Melting point / freezing point:	N/A
Initial boiling point and boiling range:	not determined
Flash point:	93 °F TCC
Evaporation rate:	not determined
Upper/lower flammability or explosive limits:	N/A
Vapor density:	not determined
Vapor pressure:	not determined
Relative density:	1.148 g/cm ³
Solubility in water:	not soluble (water)
Solubility in oil:	N/A
Partition coefficient (n-octanol/water):	N/A
Auto-ignition temperature:	N/A
Decomposition temperature:	N/A
Viscosity:	N/A
Explosive properties:	N/A
Oxidizing properties:	N/A
Solid/gas flammability:	N/A

10. STABILITY AND REACTIVITY

Reactivity

N/A

Chemical stability

Excess heating over long periods of time degrades the resin.

Possibility of hazardous reactions

Will not occur by itself, but masses of more than 1 pound of product plus an aliphatic amine will cause irreversible polymerization with considerable heat buildup.

Conditions to avoid

Avoid exposure to heat, light, flame, or other sources of ignition. Can react vigorously with strong oxidizing agents, strong lewis or mineral acids, and strong mineral and organic base/especially primary and secondary amines. Reaction with some curing agent may produce considerable heat.

Incompatible materials

None in particular.

Hazardous decomposition products

Hazardous combustion products may include intense heat, dense black smoke, carbon monoxide, carbon dioxide, as well as organic compounds of unknown structure.

11. TOXICOLOGICAL INFORMATION

Likely routes of exposure: N/A

Symptoms related to the physical, chemical and toxicological characteristics:

- Eye Contact:** Irritating and will injure eye tissue if not removed promptly.
- Skin Contact:** May cause irritation. Has been known to cause allergic skin reaction in humans. Prolonged contact may cause blisters.
- Inhalation:** High vapor concentrations are irritating to the eyes and respiratory tract, may cause headaches and dizziness.
- Ingestion:** Oral toxicity is considered to be extremely low.

Delayed and immediate effects and also chronic effects from short and long term exposure:

N/A

Numerical measures of toxicity:

Ingredient Name	CAS No.	Percent	Acute Oral LD50	Acute Oral LD50	Acute Inhalation LC50
Reaction products of epichlorohydrin and bisphenol A	25085-99-8	70-80%	>5.0 g/kg (rat)	>6.0 g/kg (rat)	Not available
Epoxy resin	28064-14-4	10-15%	>5.0 g/kg (rat)	>3.0 g/kg (rat)	>1.7 mg/L (rat)
Amorphous silica	112945-54-5	<5%	>5000 mg/kg (rat)	No data	No data
Ethanol	64-17-5	<10%	Not available	Not available	Not available

12. ECOLOGICAL INFORMATION

- Ecotoxicity:** N/A
- Persistence and degradability:** N/A
- Bioaccumulative potential:** N/A
- Mobility in soil:** N/A
- Other adverse effects:** N/A

13. DISPOSAL CONSIDERATIONS

Disposal methods: Dispose of in accordance with federal, state, and local regulations.

14. TRANSPORT INFORMATION

- UN number:** UN 1866
- UN proper shipping name:** UN 1866, Resin Solution, Flammable, 3, PG III
- Transport hazard class(es):** 3
- Packing group, if applicable:** III

Environmental hazards: N/A
Transport in bulk: N/A
Special precautions for user: N/A

15. REGULATORY INFORMATION

DSL/NDL: These items are specified in the public Portion of the Domestic Substances List:
CAS Number 28064-14-4 with Maximum Weight 15%.
CAS Number 64-17-5 with Maximum Weight 10%.

TSCA: These items are listed on the U.S. Toxic Substance Control Act:
CAS Number 64-17-5 with Maximum Weight 10%.

REACH SVHC No items in this product are on REACH's list of Substances of Very High Concern

EINECS: All components are included in the EINECS inventories.

SARA Title III: This product is not subject to the reporting requirements of SARA Title III Section 313.

16. OTHER INFORMATION

HMIS RATING Health 2, Flammability 3, Reactivity 0, Personal Protection B

NFPA RATING Special Hazard: N/A, Health: 2, Flammability: 3, Instability: 0

SDS Updated **2020-03-27**

Disclaimer

OTHER INFORMATION: This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process. Such information is to the best of the company's knowledge and believed accurate and reliable as of the date indicated. However, no representation, warranty or guarantee of any kind, express or implied, is made as to its accuracy, reliability or completeness and we assume no responsibility for any loss, damage or expense, direct or consequential, arising out of use. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use.

SAFETY DATA SHEET

May be used to comply with OSHA Hazcom 29 CFR 1910.1200. Standards must be consulted for specific requirements.

Revision Date: 2020-03-27

1. IDENTIFICATION

Product identifier

Product Name: Statguard Flooring 8403 Conductive Epoxy Adhesive, Part B

Recommended use of the chemical and restrictions on use

Identified use: Polyamine Hardener

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Supplier: MILAMAR COATINGS, INC
311 NW 122ND STREET, SUITE 100
OKLAHOMA CITY, OK 73114
405-755-8448

Email Address: Service@StatguardFlooring.com

Emergency 24 hour telephone number

Domestic Emergency Number 1-800-255-3924

International Emergency Number 1-813-248-0585

2. HAZARDS IDENTIFICATION

Classification of substance or mixture

Flammable liquid	Category 3
Acute Toxicity (Dermal)	Category 3
Acute Toxicity (Oral)	Category 3
Acute Toxicity (Inhalation)	Category 4
Skin Corrosion/Irritant	Category 3
Eye Damage/Irritation	Category 3

Label elements

Hazard pictograms/Symbols:



Signal word:

WARNING!

Hazard statements:

Flammable liquid and vapor.
Causes severe skin burns and eye damage.
Harmful if inhaled.

Precautionary statements:

Prevention

Keep away from heat/sparks/open flames/hot surfaces. No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Wear protective gloves/eye protection/face protection.
Do not breathe dusts or mists.
Wash hands thoroughly after handling.
Avoid breathing dust/fume/gas/mist/vapors/spray.
Use only outdoors or in a well-ventilated area.

Response

If on skin (or hair): remove/take off immediately all contaminated clothing. Rinse skin with water/shower. In case of fire: use carbon dioxide, foam, dry chemical or water fog to extinguish fire.

If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.

Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Call a physician if irritation persists. Wash contaminated clothing before reuse.

If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a poison center or doctor/physician.

If in eye: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If inhaled: remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.

Storage

Store in a well-ventilated place. Keep cool.
Store locked up.

Disposal

Dispose of contents/container in accordance with applicable regulations.

3. COMPOSITION/INFORMATION ON INGREDIENTS

This product is a mixture. Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

Components	CAS No.	Concentration
Polyamine Adduct	PROPRIETARY	60 - 70%
Methanol	67-56-1	< 10%
Ethanol	64-17-5	< 10%
Carbon Black	1333-86-4	10 - 15%

4. FIRST AID MEASURES

Description of first aid measures

General advice:

First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation:

Remove victim to fresh air if effects occur. If not breathing, give artificial respiration. Get immediate medical attention.

Skin Contact

Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Call a Physician if irritation persists. Wash clothing before reuse. Contaminated Leather Articles, including shoes, cannot be econtaminated and should be destroyed to prevent reuse.

Eye Contact:

Remove contact lenses at once. Immediately flush eyes with large amounts of water or normal saline for at least 30 minutes. Hold eyelids apart while flushing to rinse entire surface of eye and lids with water.

Ingestion

Do not induce vomiting. If patient is conscious and can swallow, give two glasses of water (16oz.) Get immediate medical attention. Never give anything by mouth to an unconscious or convulsing person.

Most important symptoms and effects, both acute and delayed

Signs and Symptoms: Irritation as noted above. Skin sensitization (allergy) may be evidenced by rashes, especially hives.

Aggravated medical conditions: preexisting skin and eye disorders may be aggravated by exposure to this product. Preexisting skin and lung allergies may increase the chance of developing increased allergy symptoms from exposure to this product.

Other Health Effects: Based on animal studies, repeated exposure to components of this product may cause damage to liver, kidney, and respiratory systems. Reports have associated repeated and prolonged occupational exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling vapors may be harmful or fatal.

Indication of any immediate medical attention and special treatment needed

Contact a poison control center for additional treatment information. As a precaution, exposure to liquids, vapors, mists, or fumes should be minimized.

5. FIREFIGHTING MEASURES

Extinguishing media

Suitable Extinguishing Media Use alcohol type foam, dry chemical, or CO₂.

Unsuitable Extinguishing Methods None known

Special hazards arising from the substance or mixture

Flash Point is 54°F TCC.

Advice for firefighters

Fire Fighting Procedures: Use water spray to cool fire Exposed surfaces and to protect personnel. If a leak or spill has not ignited, use ER spray to disperse the vapors. Contain the runoff stream. Try to cover liquid pills with foam.

Special protective equipment for firefighters: Do not enter confined fire space without full bunker gear (helmet with face shield, bunker coats, gloves, and rubber boots), including a positive pressure IOSH approved self contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Ventilate the area.

Avoid breathing vapor.

Use self-contained breathing apparatus or supplied air for large spills or confined areas.

See protective measures under point 7 and 8

Methods and materials for containment and cleaning up

Contain spill if possible.

Wipe up or absorb on suitable material and pick up with shovels.

Do not use sawdust, wood chips, or other cellulosic materials to absorb the spill.

Prevent entry into sewers and waterways.

Dispose of in accordance with federal, state, and local regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Ground all transfer equipment.

Take precautionary measures against static discharge.

Handle as an industrial chemical.

See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Keep container tightly closed when not in use. Practice good caution and personal cleanliness to avoid skin and eye contact. Hold bulk storage under nitrogen blanket. Store in a cool, dry place with adequate ventilation. Keep away from open flames and high temperatures.

See SECTION 8, for types of ventilation required.

8. EXPOSURE CONTROL / PERSONAL PROTECTION

Control parameters

Components	CAS No.	Exposure Limits	Source
Polyamine Adduct	PROPRIETARY	None established	
Methanol	67-56-1	200 ppm (TWA)	OSHA
Ethanol	64-17-5	1000 ppm (TWA)	OSHA
Carbon Black	1333-86-4	None established	

Appropriate engineering controls: N.A.

Individual protection measures

Eye/Face Protection	Use close fitting safety goggles, don't use eye lens.
Skin Protection	Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.
Hand Protection	Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.
Respiratory Protection	Provide adequate ventilation. Avoid breathing of vapors or mists. Airborne concentrations should be kept to lowest levels possible. When exposures are not adequately controlled, use an approved respirator. Selection of air-purifying or positive-pressure supplied air will depend on the specific operation and the potential airborne concentration of material. For emergency conditions, use an approved positive-pressure self-contained breathing apparatus.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state:	Liquid
Appearance and color:	Black paste
Odor:	Little to no odor
Odor threshold:	N/A
pH:	N/A
Melting point / freezing point:	N/A
Initial boiling point and boiling range:	not determined
Flash point:	54 °F TCC
Evaporation rate:	not determined
Upper/lower flammability or explosive limits:	N/A
Vapor density:	not determined
Vapor pressure:	not determined
Relative density:	0.99 g/cm ³
Solubility in water:	not soluble (water)
Solubility in oil:	N/A
Partition coefficient (n-octanol/water):	N/A
Auto-ignition temperature:	N/A
Decomposition temperature:	N/A
Viscosity:	N/A
Explosive properties:	N/A
Oxidizing properties:	N/A
Solid/gas flammability:	N/A

10. STABILITY AND REACTIVITY

Reactivity

N/A

Chemical stability

Excess heating over long periods of time degrades the resin.

Possibility of hazardous reactions

Will not occur by itself.

Conditions to avoid

Avoid exposure to heat, light, flame, or other sources of ignition. Can react vigorously with strong oxidizing agents.

Incompatible materials

None in particular.

Hazardous decomposition products

Hazardous combustion products may include intense heat, dense black smoke, carbon monoxide, carbon dioxide, as well as organic compounds of unknown structure.

11. TOXICOLOGICAL INFORMATION

Likely routes of exposure: N/A

Symptoms related to the physical, chemical and toxicological characteristics:

Eye Contact: Irritating and will injure eye tissue if not removed promptly.

Skin Contact: May cause irritation. Has been known to cause allergic skin reaction in humans. Prolonged contact may cause blisters.

Inhalation: High vapor concentrations are irritating to the eyes and respiratory tract, may cause headaches and dizziness.

Ingestion: Oral toxicity is considered to be extremely low.

Delayed and immediate effects and also chronic effects from short and long term exposure:

N/A

Numerical measures of toxicity:

Ingredient Name	CAS No.	Percent	Acute Oral LD50	Acute Oral LD50	Acute Inhalation LC50
Polyamine Adduct	Proprietary	60-70%	<=2.0 g/kg (rat)	<=2.0 g/kg	<=5.0 mg/L
Methanol	67-56-1	<10%	2000 mg/kg (rabbit)	Not available	Not available
Ethanol	64-17-5	<10%	Not available	Not available	Not available
Carbon Black	1333-86-4	10-15%	>8.0 g/kg (rat)	Not available	Not available

12. ECOLOGICAL INFORMATION

Ecotoxicity: N/A

Persistence and degradability: N/A

Bioaccumulative potential: N/A

Mobility in soil: N/A

Other adverse effects: N/A

13. DISPOSAL CONSIDERATIONS

Disposal methods: Dispose of in accordance with federal, state, and local regulations.

14. TRANSPORT INFORMATION

UN number: UN2924

UN proper shipping name: UN 2924, Flammable Liquid, Corrosive, nos, 3(8), PG II, (methanol and polyamines)

Transport hazard class(es): 3(8)

Packing group, if applicable: II

Environmental hazards: N/A

Transport in bulk: N/A

Special precautions for user: N/A

15. REGULATORY INFORMATION

SARA Title III:	These items are listed and subjected to the reporting requirements of the SARA Title III Section 313 Inventory of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR37: CAS Number 67-56-1 with Maximum Weight 10%.
California proposition 65:	These items are listed in the California Safe Drinking Water and Toxic Enforcement Act: CAS Number 67-56-1 with Maximum Weight 10%. CAS Number 1333-86-4 with Maximum Weight 15%.
TSCA:	These items are listed on the U.S. Toxic Substance Control Act: CAS Number 67-56-1 with Maximum Weight 10%. CAS Number 64-17-5 with Maximum Weight 20%. CAS Number 1333-86-4 with Maximum Weight 15%.
DSL/NDSL:	These items are specified in the public Portion of the Domestic Substances List: CAS Number 67-56-1 with Maximum Weight 10%. CAS Number 64-17-5 with Maximum Weight 10%. CAS Number 1333-86-4 with Maximum Weight 15%.
REACH SVHC:	No items in this product are on REACH's list of Substances of Very High Concern.
EINECS:	All components are included in the EINECS inventories.

16. OTHER INFORMATION

HMIS RATING	Health 2, Flammability 3, Reactivity 0, Personal Protection B
NFPA RATING	Special Hazard: N/A, Health: 2, Flammability: 3, Instability: 0
SDS Updated	2020-03-27

Disclaimer

OTHER INFORMATION: This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process. Such information is to the best of the company's knowledge and believed accurate and reliable as of the date indicated. However, no representation, warranty or guarantee of any kind, express or implied, is made as to its accuracy, reliability or completeness and we assume no responsibility for any loss, damage or expense, direct or consequential, arising out of use. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use.