



- A. This self-adhesive tape is suitable for marking the boundaries of ESD Protected Areas.
- B. It adheres very well to synthetic floors such as PVC tiles.
- C. The tape will also adhere to concrete floors and can be expected to remain intact for several months depending on traffic.
- D. The tape is yellow and printed in black with the ESD logo as per EN 61340-5-1 and the text 'ESD Protected Area'.
- E. The carrier tape is laminated with a clear film to protect the print. The tape is not antistatic as it is intended for use outside the EPA.
- F. The tape is a highly visible identification of the boundaries of an EPA.
- G. Available in two designs.

EN 61340-5-1 paragraph 4.3 Signs for ESD protected areas (EPA)
 ESD sensitivity symbol "Sign(s) ...shall be clearly visible to personnel before they enter the EPA and, where applicable, from inside the EPA."
 Where applicable, signs ... shall mark the EPA boundary."

Paragraph 4.4 Marking of EPA bonding points (EBP) "All EBP shall be marked or labelled."

Per EN 61340-5-2 paragraph 5.1.1 "The boundaries of the EPA need defining and will vary between different types of EPA, but will typically have coloured (but not electrostatic generative) markings on the floor."

Specifications and procedures subject to change without notice.

Item	Description
210300	Floor Marking Tape, 75mm wide, 33m long
210310	Floor Marking Tape with Arrows, 50mm wide, 66m long

Tolerance ±5 mm



Made in the United Kingdom

Floor Marking Tape

DESCO EUROPE

DESCO EUROPE
 2A DUNHAMS LANE, LETCHWORTH GARDEN CITY,
 HERTFORDSHIRE, SG6 1BE, UK
 PHONE: +44 (0) 1462 672005
 E-MAIL: Service@DescoEurope.com, INTERNET: DescoEurope.com

Drawing Number
 210300

DATE:
 December
 2017