



Features



- Economical method of storing static sensitive electronics devices
- Wide choice of sizes
- When reclosable cover is closed, the “Faraday Cage” effect restricts electrostatic charges to exterior of box
- Shipped knocked-down; easy to assemble

| Item No. | Size O.D. - L x W x D |
|------------------------|-----------------------|
| 37590 | 12 x 4 x 4-1/2 |
| 37591 | 12 x 6 x 4-1/2 |
| 37599• | 12 x 8 x 4-1/2 |
| 37592 | 12 x 12 x 4-1/2 |
| 37593 | 18 x 4 x 4-1/2 |

| Item No. | Size O.D. - L x W x D |
|------------------------|-----------------------|
| 37594 | 18 x 6 x 4-1/2 |
| 37598• | 24-3/4 x 2 x 4-1/2 |
| 37595 | 24-3/4 x 4 x 4-1/2 |
| 37596 | 24-3/4 x 6 x 4-1/2 |
| 37597• | 24-3/4 x 8 x 4-1/2 |

• These items are made to order

Meets the required limits of ANSI/ESD S20.20, and Packaging standard ANSI/ESD S541.

SPECIFICATIONS

Properties
Surface Resistance
Discharge Shielding
Sloughing Test

Typical Values
 1×10^6 to $< 1 \times 10^9$ ohms
 < 50 nanoJoules
 Negligible surface damage at 10 cycles and <5% of surface damage at 200 cycles in Taber Abrasion Test.
 No conductive particles abraded from surface
 Complete recyclability of package

Test Procedures/Method
 ANSI/ESD STM11.11
 ANSI/ESD STM 11.31
 ASTM D4060 at 70 rpm with CS-17 abrasive-coated wheels and 1000 grams load
 Rockwell International Test Report of January 8, 1992
 Rockwell International Test Report of January 8, 1992

Recyclability

RoHS, REACH, and Conflict Minerals Statement
 See the Desco Industries RoHS, Reach, and Conflic Minerals Statement: <http://www.descoindustries.com/ROHS.aspx>
 See the Protektive Pak Limited Warranty: <http://protektivepak.descoindustries.com/Limited-Warranty.aspx>



Made in the United States of America

Specifications and procedures subject to change without notice

Unless otherwise noted, tolerance is ±10%

| | | |
|--|--|--------------------------------|
| | CLOSED BIN BOXES | |
| | PROTEKTIVE PAK 13520 MONTE VISTA AVENUE, CHINO, CA 91710 PHONE (909) 627-2578 ProtektivePak.com | DRAWING NUMBER 37590 |