



RoHS Compliance Statement

As outlined in the Directive (EU) 2015/863 the following materials have not been intentionally added during the manufacture of this product:

Benzyl butyl phthalate (BBP)	Lead (Pb)
Hexavalent Chromium: (Cr VI)	Mercury (Hg)
Polybrominated Biphenyls (PBB)	Cadmium (Cd)
Bis(2-Ethylhexyl) phthalate (DEHP)	Dibutyl phthalate (DBP)
Polybrominated Diphenyl Ethers (PBDE)	Diisobutyl phthalate (DIBP)

Structure:

Heat laminated, multi-layer PVC with protective top coating. Structure is indicated by diagram below.

Electrical Properties:

Item	Specification	Unit	Testing Method
Surface of color layer	1×10^6 to $< 1 \times 10^9$	Ohms	ANSI/ESD STM7.1
Black layer	$< 1 \times 10^6$	Ohms	ANSI/ESD STM7.1

Physical Properties:

Item	Specification	Unit	Testing Method
Thickness	2.0	mm	
Tensile Strength (Vertical, Horizontal)	9 Minimum	MPa	JIS K 7113 Tensile Speed 500m/min
Elongation Percentage (Vertical, Horizontal)	60 Minimum	%	JIS K 7113 Tensile Speed 500m/min
Hardness (Type A)	86~98	-	JIS K 7215
Abrasion	150 Maximum	mg	JIS K 7204 Wear Wheel S42
Indentation (20,45)	0.3~1.5	mm	JIS A 1454

Grounding:

This material must be properly grounded for optimum electrical performance. See items [3090 Snap](#) and [3040 Ground Cord](#).

Coated PVC Dissipative Runner

Item	Color	Width	Length
9602C	Beige	1820mm	9.2m
9609C	Green	1820mm	9.2m

Matting materials have a tendency to shrink slightly when first unrolled. In applications where length is critical, allow the material to relax for at least 4 hours before cutting to size. Carefully trim with a sharp knife or razor blade.

NOTE: For applications on smooth floors, Ask for [item 45015](#) Two Side Adhesive Tape to safely secure product on table tops and floors.

Thickness tolerances +/-0.2mm
 Length tolerances +0.5m, -0m
 Width tolerances +20mm, -0mm
 Unless otherwise noted tolerances +/- 10%

Made in Japan

Color and texture may vary between lots and mills
 Specifications and procedures subject to change without notice.

9600 Series Dissipative PVC Flooring Sheet

661-1 Yachimata-ho
 Yachimata City, Chiba, 289-1115 Japan
 PHONE: 81-43-309-4470 FAX: 81-43-332-8741
 WEBSITE: DescoAsia.com

Drawing Number
9602C

DATE:
November
2017

DESCO ASIA