

SelecTech, Inc.
33 Wales Ave, Unit F
Avon, MA 02322

FreeStyle, FreeStyle Bio-Lock &
SelecTile
Resilient Tile Flooring Products
MATERIAL SAFETY DATA SHEET

I. PRODUCT IDENTIFICATION

Name: SelecTech Resilient Tile Flooring Products. Description: Vinyl Flooring

II. DEPARTMENT OF TRANSPORTATION INFORMATION

Shipping Name: Not classified. Hazard Class: N/A. ID #: N/A

Emergency Telephone: 508.583.3200 Regular Telephone: 508.583.3200

III. HMIS 0=minimal hazard; 4=severe hazard

Health=0 Flammability=1 Reactivity=0

IV. PRODUCT CONTENT

This products does not contain chemicals subject to the reporting requirements of Section 313 of SARA Title III and 40 CFR 372. All components are on TSCA inventory.

V. HAZARDOUS INGREDIENTS

Chemical Identity: None CAS #: N/A %: N/A OSHA PEL: N/A ACGIH TLV: N/A

DESCRIPTION AND INGREDIENT INFORMATION

These vinyl flooring products are produced from plasticized vinyl and post-industrial vinyl scrap and are manufactured for residential and commercial use.

MISCELLANEOUS INFORMATION

Each of these products is classified as an "article" under Title 29 of the Code of Federal Regulations. They are formed to a specific shape or design during manufacture, have end use functions dependent upon their shape or design, and do not release any hazardous chemical under normal conditions of use.

VI. PHYSICAL DATA

| | | |
|----------------------------------|------------------------------|--------------------------------------|
| APPEARANCE: Waxy solid | SOLUBILITY IN WATER: N/A | PERCENT VOLATILE BY VOLUME: (%) <0.4 |
| BOILING POINT: (degrees F): N/A | ODOR: Mild Characteristic | EVAPORATION RATE: N/A |
| VAPOR PRESSURE (-mm Hg 20C): N/A | MELTING POINT: 482 C (482 F) | PH: N/A |
| VAPOR DENSITY (AIR=1) N/A | SPECIFIC GRAVITY: N/A | VOC: N/A |

VII. FIRE AND EXPLOSION DATA

| | |
|---------------------------------------|---|
| FLASH POINT: N/A | SPECIAL FIREFIGHTING PROCEDURES: Protect firefighters from toxic products of combustion by wearing self-contained breathing apparatus |
| FLAMMABLE RANGE: LEL = N/A; UEL = N/A | UNUSUAL FIRE AND EXPLOSION HAZARDS: None. |
| EXTINGUISHING MEDIA: water | |

VIII: HEALTH HAZARDS

PRIMARY ROUTES OF ENTRY: N/A. TARGET ORGANS: N/A. EFFECTS OF OVEREXPOSURE: N/A. SKIN AND EYES: N/A. INHALATION; N/A. CARCINOGENICITY: NTP: No; IARC Monographs: No; OSHA Regulated: No. MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: N/K. FIRST AID PROCEDURES: N/A. SKIN AND EYES: N/A. INGESTION: N/A

IX. REACTIVITY DATA

STABILITY: N/A. INCOMPATIBILITY: N/A. HAZARDOUS DECOMPOSITION PRODUCTS: N/A. HAZARDOUS POLYMERIZATION: N/A

X. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: N/A. WASTE DISPOSAL METHOD: Dispose of in accordance with Federal, State, and Local Waste Disposal Regulations

XI. SAFE HANDLING AND USE INFORMATION

EYE PROTECTION: When cutting or drilling. PROTECTIVE GLOVES: When handling hot material. VENTILATION: When cutting or sanding approved dust respirators must be worn. VENTILATION: Use adequate ventilation when cutting or sanding.

XII. WARNING

FOR INSTALLATION OVER EXISTING RESILIENT FLOOR COVERING

DO NOT SAND, DRY SCRAPE, BEADBLAST, OR MECHANICALLY PULVERIZE EXISTING RESILIENT FLOORING, BACKING OR LINING. THESE PRODUCTS MAY CONTAIN EITHER ASBESTOS FIBERS OR CRYSTALLINE SILICA. POSSIBLE CANCER AND RESPIRATORY TRACT HAZARD BY INHALATION. AVOID CREATING DUST. SMOKING BY INDIVIDUALS WHO HAVE BEEN EXPOSED TO ASBESTO FIBERS GREATLY INCREASES THE RISK O SERIOUS BODILY HARM. RFCI'S (Resilient Floor Covering Institute) RECOMMENDED WORK PRACTICES FOR REMOVAL OF RESILIENT FLOOR COVERINGS ARE A DEFINED SET OF INSTRUCTIONS ADDRESSED TO THE TASK OF REMOVING ALL RESILIENT FLOOR COVERING STRUCTURES.

NOTICE:

The information presented herein is supplied as a guide to those who handle or use this product. Safe work practices must be employed when working with any materials. It is important that the end user makes a determination regarding the adequacy of safety procedures employed during use of this product.