

# STATICO

---

## Product Specifications for S101-09 & S101-12 Static Dissipative PP Strap



### Specifications

<b>Material</b>	<b>Polypropylene Co-Polymer</b>
<b>Color</b>	<b>Black</b>
<b>Resistance</b>	<b><math>10^5</math>-<math>10^8</math> ohm/sq</b>
<b>Standard Roll Sizes</b>	<b>9mm (0.354") Wide x1200 Meter (3937') Long</b> <b>12mm (0.472") Wide x 1500 Meter (4895') Long</b>
<b>Thickness</b>	<b>0.025" (0.6mm, +/-0.1mm)</b>
<b>Melting Point</b>	<b>338° F, +/-41° F (170° C, +/-5° C)</b>
<b>Tensile Strength</b>	<b>72.0 MPA (Before Bake) &amp; 68 MPA (After Bake)</b>
<b>Core Diameter</b>	<b>7" (200mm)</b>
<b>Features</b>	<b>*Minimum Shrinkage of Straps after baking process</b> <b>*Compatible with most strapping machines</b> <b>*Excellent electrical properties</b>
<b>Application</b>	<b>Suitable for Strapping of IC trays/tubes during burn-in test and transportation</b>

**Note:** Tolerances +/- 10%