STATICO

Product Specifications for S1504 Series Multi-Layer Table/Floor Matting



Description

S1504 Series is a multi-layer static dissipative matting constructed of solid Vinyl, designed for applications as table or floor mats in static free work areas. This product with its excellent electrical & physical properties offers a unique single solution for static safe table or floor coverings in the areas where ESDS (Electro Static Discharge Sensitive) components/devices are handled. This product meets and exceeds ANSI/ESD S20.20-2014.

Specifications (1)

Colors Dark Grey & Blue KidGrain (Cast on

Emboss Patterns KidGrain (Cast on leatherette-embossed Paper)

Gauge 0.094"± 0.010" (3/32" or 94 mils)

Standard Roll Size 24"x 50'; 30"x50'; 36"X50' & 48"X50' (Available in custom Sizes on request)

Tensile (ASTM D412) 900 lb/in² Minimum

Elongation (ASTM D412) 125%

Tear (ASTM D1004) 150 lb/in Minimum Durometer (ASTM D2240-75) 85 ± 5, Shore A Resistance (ESD S4.1 & S4.2)

Rtg (@ 10V, 12% RH) $3.0 \times 10^7 - 9.5 \times 10^8 \text{ Ohms}$

Decay Time (EIA 541) <2.0 Seconds
Suggested Service Temperature (2) -20°F to +160°F

Due to the variety of possible end-uses, it is ultimately the responsibility of the customer to determine a product's suitability for a particular application.

⁽¹⁾ Specifications are subject to change at any time for a variety of reasons. If you have any questions, Please call for the latest update.

⁽²⁾ This suggested range represents the general temperature range for most flexible vinyl products.