

# Product Specifications for S2771 & S2772 Workstations Monitoring System



# **Description**

The S2771 & S2772 are Constant Monitoring systems for Single Operator/Station or Two-Operator/Station. Both Systems are Impedance-Base Monitors which are designed to work with Dual Conductor Wrist Straps.

## System Features

- S2771 Monitors Single-Operator Wrist Strap; ESD Mat & Ground Connection.
- S2772 Monitors Wrist Straps of Two Operators; ESD Mats & Ground Connections.
- Both Systems eliminate the common problem of fooling the conventional impedance/Capacitance-Base \*
  - monitoring systems, through employing the Loop-Design & Dual Conductor Wrist Straps.
    - \* Conventional Impedance/Capacitance-Base Monitors, using Single-Conductor Wrist Straps, can be fooled by Stretching or Squeezing the
- wrist strap cord. Both systems are designed for real-time monitoring of Wrist Strap, ESD Mat & Ground Connection.
- Pass & Fail Status are demonstrated by both Audio & Visual indicators.
- The Dual-Conductor Wrist Strap offers benefit of 2 wrist straps for each user.
- The Dual-Conductor Wrist Strap offers an immediate replacement of a good strap, when one of the conductors lose their properties and goes bad.
- The Monitor gives audio/visual Pass or Fail indication for each conductor of individual wrist straps separately.
- Integrity of Wrist Strap is individually Monitored for each Conductor separately, and Pass/Fail status is indicted via Green/Red LEDs & Audio Alarm.
- Audio/Visual Alarm//Indicator when the Ground Connection is lost.

#### **Electrical Specifications**

- Operator Resistance Range R<6.8 M, +/- 10%
- Ground System Range : R<6.8 M, +/- 10%
- Maximum Wrist Strap Voltage 2V DC
- Maximum Wrist Strap Current1.6 mA DC
- Maximum Mat Voltage 4V DC
- Maximum Mat Current 1.8 mA DC

## Mechanical Specifications

- S2771 : 3-1/2"L X 2-1/2"W X 1" H (90mm L X 65mm W X30 mm H)
- S2772 : 7-1/4"L X 3"W X 1-1/4" H (160mm L X 75mm W X 30mm H)

## System Parts

- S2771 Includes:
  - 1 Each The Monitor
  - 1 Each An Adapter
  - 1 Each A Connection Cord (Monitor-To-Mat); 81" L (2060mm)
  - 1 Each A Remote Connection Cord (Wrist Strap-To-Monitor); 70" (1780mm)
  - 2 Each 2" L X1" W (50mm L X 30mm W) Hook & Loop Velcro pcs
  - 2 Each Screws
  - 1 Each Alligator Clip
  - 1 Each a Dual Conductor Wrist Strap with 6' Coil Cord (Also available with 12' Coil Cord).
- S2772 Includes:
  - 1 Each The Monitor
  - 1 Each An Adapter
  - 1 Each A Connection Cord (Monitor-To-Mat); 81" L (2060mm)
  - 2 Each A Remote Connection Cord (Wrist Strap-To-Monitor); 70" (1780mm)
  - 2 Each 2" L X1" W (50mm L X 30mm W) Hook & Loop Velcro pcs
  - 2 Each Screws
  - 1 Each Alligator Clip
  - 2 Each a Dual Conductor Wrist Strap with 6' Coil Cord (Also available with 12' Coil Cord).