



### Description

Conductive Cart Covers control electrostatic discharge while protecting cart contents from contamination and moisture. These covers leave no black carbon residue and clean easily with mild soap and water. The cart covers are also flame retardant and resist the growth of bacteria, fungus, and mildew. Includes velcro ties for corner posts, and flap closures.

Color: Black with light blue backing

### Electrical Properties

Surface Resistance (blue side):  $10^7 - 10^8$  ohms per ESD S4.1

Surface Resistance (black side):  $10^3 - 10^4$  ohms per ESD S4.1

### Physical Properties

Resistance to Fungi

No growth per ASTM G-21-90

Weight

13 oz/sq yd (60 lbs/roll)

Grab Tensile

140-150 lbs per Fed Test Std 191b, Method 5100

After Flame

2.0 seconds

Char Length

0.3 inches

Flame Resistance

Pass per Motor Vehicle Safety Standard 302

Horizontal Burn Test

Hydrostatic Bust Test - Mullen

190 psi per Fed Test Std 191, Method 5512

Item No.	Description (DxWxH)
17900	Cart Cover, 18" x 36" x 63"
17901	Cart Cover, 18" x 48" x 63"

### Cart Cover, Conductive



432 NORTHBORO ROAD CENTRAL  
MARLBORO, MA 01752-3170  
PHONE (508) 485-7390  
FAX (508) 480-0257



Visit our online  
library of Tech Drawings:  
<http://www.esdsystems.com>

**DRAWING NUMBER**

**TD-17900**

**DATE**

**7/05**