



WRIST STRAP:

- A. Machined 0.160" (4mm) stud, 300 series stainless steel. To fit 1/8" (4mm) spring loaded medical snap socket.
- B. Easy to open plastic clasp secures elastic material in place, and allows the user to easily adjust the wrist band size. Maintains electrical continuity even when open.
- C. Non-allergenic stainless steel base plate, provides excellent skin contact, for superior grounding.
- D. Insulating cap, thermoplastic.
- E. Soft elastic band.

GROUND CORD:

- F. Barrel type banana plug. Fits industry standard banana jack 0.166 in. (4.22mm).
- G. Metallized, high flex tinsel, black jacket.
- H. One megohm, 1/4 watt, series resistor, molded within snap assembly, limits current for operator safety.
- I. Spring loaded snap socket.
- J. Alligator clip included.
- K. Date coded with date of manufacture.

ITEM #	DESCRIPTION
22310	Band with 5' Coil Cord, 4mm
22311	Band with 5' Coil Cord, 7mm

The color of the band material may vary.

Wrist Strap Kit, Elastic, Adjustable, Economy

ESD SYSTEMS.com

ESD SYSTEMS.COM
 432 NORTHBORO ROAD CENTRAL
 MARLBORO, MA 01752 USA
 TEL. (508) 485-7390 FAX (508) 480-0257



Visit our online
 library of Tech Drawings:
<http://www.ESDSystems.com>

DRAWING NUMBER
TD-22310

DATE
February 2009